

Fueling Advanced Intelligent Transportation Systems

LocoMate[™] OBU On-Board Unit

Key Benefits

Hardware

- Wireless access for vehicular environment
- 5.700 to 5.925 GHz frequencies
- 10 MHz and 20 MHz channel bandwidth
- · Options for 2 DSRC radio
- Utilize radios designed by Arada Systems
- High throughput capability for varied applications
- Efficient handling of WSMP (WAVE Short Messaging Protocol) and IP traffic

Software

- WAVE Standards Support
 - -802.11p
 - 1609.2
 - 1609.3
 - 1609.4
 - SAE J2735
- Fast channel switching capabilities
- Switching capability between control and service channels
- Multi-channel synchronization between service users
- · Exclusive packet control
 - TX power control per packet
 - Data rate control per packet
- Remote application support
- Software development kit (SDK) for application development

WAVE Mode

- Support for 5.9 GHz spectrum with 10 MHz channel width
- Support for WAVE data and management frames
- Support for multi channel (control channel and service channel) using single radio
- <= 3 mS channel switch time irrespective of traffic conditions
- Can preempt messages in transmit
 queue
- Support for multiple priority queues
- Support for GPS-based synchronization





Intelligent Transportation systems America Member



Appro US Dep Transpor Qualify P



proved The
Dept of Com
portation Co
fy Product N
Vendor



The CAR-2-CAR Communication Consortium Member



WAVE standard support 1609.2 1609.3, 1609.



SAE J2735 Support



upport for Mobile



Dedicated Shor Range 5.9 Communication



Product Highlights

An integration of GPS and Wi-Fi, LocoMate[™] OBU is ideal for telematic applications by allowing vehicles on the road to talk to each other or to another road side unit. It is fully compliant with Omni-Air's certification and is used in worldwide deployments including the US Department of Transportations' Safety Pilot in Ann Arbor, Michigan. Product applications include: Collision Avoidance, Emergency Vehicle Management, Train Crossing, Tolling, Commerce Applications (\$), Truck Platooning, Taxi Management and Geo-Fencing.

LocoMate OBU comes in a small form factor for in-vehicle deployment and comes with a full DSRC WAVE software solution and applications for integration with Smart Phones to ease the human-user-interface. The solution comes integrated with GPS (with better than 1 meter accuracy), Bluetooth and high-power 802.11p radios.

Specifications DATA SHEET | LocoMate™ OBU

Protocols

- 802.11p (WAVE)
- EEE 1609.2
- IEEE 1609.3
- IEEE 1609.4
- SAE J2735

Frequency

- · 5.85 5.925 GHz
- 5.7 5.8 GHz (Europe)

DSRC Radio

· High power miniPCI optimized for 5.9 GHz

GPS Device

- · GPS with external RF antenna
- Accuracy <1m

Bluetooth

 OBU – Bluetooth radio allows sniffing Bluetooth radios around the OBU

Multi-channel operation

· Consistent 3 mS channel switch time

Supplementary 802.11 MAC features

- Control Channel (CCH) and Service Channels coordination
- · 50 mS channel dwell time
- CCH for broadcast, high-priority and single-use safety messages and SCH for IP data

Output Power

 5.9 GHz: +23dBm at 64QAM from -40°C to +85°C

Platform

- · Linux/Unix compatible
- · SDK with C libraries

Database Configuration

- CLI
- Database file backup, restore

Platform

- · Linux/Unix compatible
- SDK with C libraries

Channel Access

· Alternative, continuous

Channel Switching

• Consistent 3 mS switch time at every 50 mS

Software Queuing

- Transmit queues per channel
- Prioritized channel access queues, with configurable channel access parameters

Interactive Communication

ssh/telnet

Network Protocol

ipv4 / ipv6

Network Configuration

- Wired and DSRC
- · ipv4 configuration
- · ipv6 configuration
- · SIT Tunnel Support

US DOT VAD spec

QPL vendor

GPS Applications

- · Approx. 1m accuracy
- · Path history implementation
- · Path prediction implementation

Local Time Synchronization

· GPS along with PPS

Security

- Signing and verification of messages, encryption and decryption of messages
- Signing and verification of WSAs

Message Logging

- DSRC Transmit packets, DSRC Receive Packets, Ethernet packets
- · System events
- Heartbeat messages with configuration (ipv4 or ipv6)
- Log offload configuration (ipv4 or ipv6)
- Wave Service Announcement configuration

LFDs

- · DSRC packet transmission
- Firmware upgrade
- USB storage access

Software Development Kit

- · Linux based tool chain
- · Application library
- · Sample applications
- Programmer guide
- User guide
- · SAE J2735 ASN library
- Sample applications include the following J2735 message formats: BSM, SPAT, MAP, TIM
- Sample applications include GPS data extraction

Data and Management Planes

- UDP/TCP and WAVE Short Messaging Protocol (WSMP) support
- Manages WAVE Basic Service Set (WBSS)
- Application management

Channel Bandwidth

 WAVE mode (802.11p) at 5.9 GHz: reduced to 10 MHz, supports 20 MHz channels

DSRC Message Set - SAE J2735

- BSM Port I, BSM Port II, SAE J2735
- · SPAT, MAP, TIM

Flash/RAM

- · 16 MB Flash
- 64 MB SDRAM (512 Mbits)

Shared Library

Applications Shared Library with Windows/Linux support for application development

Applications Support

- Menu-driven tool
- IP based applications
- · WSM-based applications
- Periodic transmit of GPS data
- Remote and logging applications

Certificate Management

- 1609 certificate update
- Support for time limited 1609 certificate

DSRC Channel Support			
10 MHz Channels	Frequency (MHz)		
172	5860		
174	5870		
176	5880		
178	5890		
180	5900		
182	5910		
184	5920		
20 MHz Channels	Frequency (MHz)		
173	5865		
175	5875		
177	5885		
179	5895		
181	5905		
183	5915		

Throughput Traffic Test Results Half-Rates on Channel 172 (Mbps) Without Channel Switch								
Rates	3M	4.5M	6M	9M	12M	18M	24M	27M
ТСР	2.36	3.37	4.34	6.32	7.97	11.23	13.54	14.75
UDP	2.38	3.50	4.37	6.99	9.00	12.96	15.81	17.32

Throughput Traffic Test Results Full-Rates on Channel 175 (Mbps) Without Channel Switch				
20 MHz Data Rates	ТСР	UDP		
6M	4.7	5.0		
9M	6.7	7.2		
12M	9.8	10.5		
18M	12.9	14.52		
24M	16.6	18.661		
36M	22.630	26.022		
54M	27.782	32.231		

Specifications DATA SHEET | LocoMate™ OBU

TCP/UDP Throughput in Different Channels				
	TCP (Mbps)	UDP (Mbps)		
WAVE operation in 20 MHz (max. phy rate=54 Mbps)	27.780	32.231		
WAVE operation in 10 MHz (max. phy rate=27 Mbps)	14.75	17.32		
WAVE operation in 10 MHz, with periodic channel switch	6.9	8.6		

Average per Packet Latency Values with Different Content Type Messages				
	Plain Sign/Sign Verify			
Average packet interval with 100 mS transmit periodicity	102 mS	112 mS	139 mS	
Latency	2 mS	10 mS	35-40 mS	

802.11p Radio Specifications				
Modulation	Data Rate	TX	RX	
BPSK	3 Mbps	23±1dBm	-95±2dBm	
16QAM	18 Mbps	23±1dBm	-83±2dBm	
64QAM	27 Mbps	23±1dBm	-77±2dBm	
Other Specifications				
Antenna Interface	SMA Connector			
Operating Temperature	-40°C to +80°C (output power specified over full temperature profile)			
Channel Bandwidth	10 MHz, 5 MHz (FCC "Class C" Mask Compliant)			

Ordering Information

LocoMate Standard 200 OBU-On-Board Unit

200: Standard OBU

205 LocoMate ASD Kit (includes the standard OBU plus, quiet state board, Fakra connecter, Delphi connecter, 4 GB flash drive, surge protection compliant SAE J1113-11)

sales@arada systems.com

About Arada Systems

Arada Systems is a leader in technologies meant for vehicle-based communication networks, particularly for applications such as toll collection, vehicle safety services, and commerce transactions via cars. LocoMate[™] is being evaluated for real-time communication between vehicles and roadside access points or other vehicles creating a real-time public safety network.

